

Charnwood Borough Council Strategic Flood Risk Assessment Level 2 Detailed Site Summary Tables



Site details	Site Code	PSH120																						
	Address	Land east of Leicester Road																						
	Area	38.70 ha																						
	Current land use	Greenfield																						
	Proposed land use	Residential																						
Sources of flood risk	Topography	<p>The site generally slopes from south east to north west.</p> <ul style="list-style-type: none"> • The site is bound to the north by a railway embankment. • There are no existing buildings present within the site. • The ground slope across the site generally has a gradient of less than 5%. 																						
	Existing drainage features	An unnamed ordinary watercourse flows from the south east of the site towards the northwest where it enters the Rothley Brook. A second unnamed ordinary watercourse flows from the south and joins the other unnamed watercourse in the centre of the site.																						
	Fluvial	<table border="1"> <thead> <tr> <th colspan="4">Proportion of site at risk</th> </tr> <tr> <th>FZ3b</th> <th>FZ3a</th> <th>FZ2</th> <th>FZ1</th> </tr> </thead> <tbody> <tr> <td>15%</td> <td>15%</td> <td>17%</td> <td>83%</td> </tr> <tr> <th colspan="4">Highest zone of risk (Risk of Flooding from Rivers and Sea)</th> </tr> <tr> <td colspan="4">High</td> </tr> </tbody> </table> <p><i>The % Flood Zones quoted show the % of the site at flood risk from that particular Flood Zone/event, including the percentage of the site at flood risk at a higher risk zone, e.g. FZ2 includes the FZ3 %. FZ1 is the remaining area outside FZ2 (FZ2 + FZ1 = 100%)</i></p>				Proportion of site at risk				FZ3b	FZ3a	FZ2	FZ1	15%	15%	17%	83%	Highest zone of risk (Risk of Flooding from Rivers and Sea)				High		
Proportion of site at risk																								
FZ3b	FZ3a	FZ2	FZ1																					
15%	15%	17%	83%																					
Highest zone of risk (Risk of Flooding from Rivers and Sea)																								
High																								

Charnwood Borough Council Strategic Flood Risk Assessment Level 2 Detailed Site Summary Tables



Site details	Site Code	PSH120		
	Address	Land east of Leicester Road		
	Area	38.70 ha		
	Current land use	Greenfield		
	Proposed land use	Residential		
		<p>Available data: The site is covered by the Environment Agency's Flood Map for Planning, which uses 2D generalised modelling data. The Flood Zones are only present in the downstream extent of the drain near the Rothley Brook, because upstream the catchment is less than 3km² and not represented.</p> <p>Flood characteristics: The Flood Map for Planning presents the site to be located within Flood Zone 2 and 3 with out of bank flooding largely occurring the northern boundary of the site, at the confluence with the Rothley Brook and along this watercourse where the floodplain topography is lowest. There would also be flood risk along the remaining reach of the drain, but this is not represented in the Flood Zones. The floodplain looks fairly confined though so it is likely out of bank flooding would be within the vicinity of the channel. The unnamed ordinary watercourse which enters the site from the west near Leicester Road is also not covered by any modelling. As 2D generalised modelling methods have been used to assess the fluvial risk for the site, it is recommended that a more detailed hydraulic model is constructed at the site-specific Flood Risk Assessment stage which also includes the west unnamed ordinary watercourse, to confirm fluvial flood risk to the site.</p>		
	Surface Water	Proportion of site at risk (RoFfSW)		
		30-year	100-year	1,000-year
		6%	11%	25%
		Max depths (m)		
		>1.2	>1.2	>1.2
		Max velocity (m/s)		
		>2	>2	>2
		<p><i>The % SW extents quoted show the % of the site at surface water risk from that particular event, including the percentage of the site at flood risk at a higher risk zone (e.g. 100-year includes the 30-year %)</i></p>		

Charnwood Borough Council Strategic Flood Risk Assessment Level 2 Detailed Site Summary Tables



Site details	Site Code	PSH120
	Address	Land east of Leicester Road
	Area	38.70 ha
	Current land use	Greenfield
	Proposed land use	Residential
		<p>Description of surface water flow paths: Surface water flows follow the drains through the centre of the site from the south-eastern corner, north-west to the Rothley Brook, for all events. Further flooding extends from these watercourses into the site, particularly in the north eastern corner for the 1,000-year event, in the lower topography of the Rothley Brook floodplain. West of the ordinary watercourse, there is a surface water flow path following the other small drain from the south, meeting the main drain in the centre of the site. The depths are high in all events, because this is picking up the watercourse channel through the centre of the site. Depths are shallower moving away from the watercourse.</p> <p>RoFfSW takes account of building footprints so the flood risk may be affected by existing buildings on the site. It also only considers flood risk where the hazard rating is greater than 0.575.</p>
	Groundwater	<p>The Areas Susceptible to Groundwater Flooding dataset shows the south of the site is located within a 1 km grid square where $\geq 50\%$ $< 75\%$ of the area is predicted to be at risk of groundwater flooding. The remainder of the site is located within a 1km grid square where</p> <p>The AStGWF data should be used only in combination with other information, for example local data or historical data. It should not be used as sole evidence for any specific flood risk management, land use planning or other decisions at any scale. However, the data can help to identify areas for assessment at a local scale where finer resolution datasets exist. Ground investigations may be required at the site.</p>
	Reservoir	The available online maps show a significant reach from maximum extent of flooding from reservoirs into the top half of the site.
	Flood history	<p>The Rothley Brook flooded in 1977 resulting in flooding up to 150m from the brook/boundary into the proposed site. The site itself was not flooded during this event.</p> <p>Leicestershire County Council may hold additional records which are not available at this time. These records detail historical flood incidents from all sources, whereas the Environment Agency dataset only records incidents of fluvial, tidal or coastal flooding. The Lead Local Flood Authority should be contacted to obtain further details.</p>

Charnwood Borough Council Strategic Flood Risk Assessment Level 2 Detailed Site Summary Tables



Site details	Site Code	PSH120		
	Address	Land east of Leicester Road		
	Area	38.70 ha		
	Current land use	Greenfield		
	Proposed land use	Residential		
Flood risk management infrastructure	Defences	Defence Type	Standard of Protection	Condition
		High Ground	N/A	N/A
	High ground is located on the north west boundary for 570m, following the banks of the Rothley Brook. It is unknown what the standard of protection or condition of the high ground is.			
Residual risk	The watercourse which runs through the site is culverted under Leicester Road, Thurcaston Lane (Rothley Brook) and the A46. If the entrances to the culverts were to become blocked, water could back up and spill overland into the site and result in further flooding. Given the confined topography and A46, it is unlikely there would be significant risk from the A46 structures. This should be investigated further in a FRA.			
Emergency planning	Flood warning	The site is situated within the Environment Agency's Leicester Rothley Brook Flood Alert area (034WAF403) and East Midlands Flood Warning area (034FWFROGLENFLD).		
	Access and egress	Safe access and egress is available for the site via Leicester Road for all fluvial and surface water events. Thurcaston Lane should be avoided as the Rothley Brook is shown to flood this. However, the ordinary watercourses bisect the site, so consideration regarding access is required for the portion of the site north of the watercourse.		

Charnwood Borough Council Strategic Flood Risk Assessment Level 2 Detailed Site Summary Tables



Site details	Site Code	PSH120
	Address	Land east of Leicester Road
	Area	38.70 ha
	Current land use	Greenfield
	Proposed land use	Residential
Climate Change	Implications for the site	<ul style="list-style-type: none"> Increased storm intensities due to climate change may increase the extent, depth, velocity, hazard and frequency of both fluvial and surface water flooding. There is no detailed fluvial modelling available at the site to indicate fluvial flood risk at the site due to climate change. As part of a site-specific Flood Risk Assessment, latest EA climate change allowances will need to be considered in a detailed hydraulic model, to confirm the impact in the site. Using Flood Zone 2 (1,000-year) as a proxy for climate change, there is only a small increase in flood extent in the centre of the site. Therefore, the site is predicted to be at an increase in flood risk in the future. Climate change also needs to be considered for surface water events; at the site-specific stage, the 100-year +40% event is considered as part of surface water drainage strategies, or surface water modelling. The current day 1,000-year surface water extent provides an indication of the likely increase in extent of the more frequent events. This would require a detailed FRA to assess the site layout and design. Developers should consider SuDS strategies to reduce the impacts of climate change from surface water in a detailed site-specific FRA.
Requirements for drainage control and impact mitigation	Bedrock Geology	The entire site's bedrock geology consists of the Wealden Group (mudstone, siltstone and sandstone).
	Superficial Geology	The eastern half of the site is underlain with Till deposits consisting of diamicton and the western half is underlain by Alluvium deposits, consisting of clay, silt and sand.
	Soils	The NW half of the site has slightly acid loamy and clayey soils with impeded drainage and the other half has lime-rich loamy and clayey soils with impeded drainage.
	Source Protection Zone	The site is not located within any Environment Agency designated Source Protection Zone.
	Historic Landfill Site	The site is not designated by the Environment Agency as previously being a landfill site.

Charnwood Borough Council Strategic Flood Risk Assessment Level 2 Detailed Site Summary Tables



Site details	Site Code	PSH120
	Address	Land east of Leicester Road
	Area	38.70 ha
	Current land use	Greenfield
	Proposed land use	Residential
	Broad scale assessment of possible SuDS	<p>Implementation of SuDS at the site could provide opportunities to deliver multiple benefits including volume control, water quality, amenity and biodiversity. This could provide wider sustainability benefits to the site and surrounding area. Proposals to use SuDS techniques should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible constraints.</p> <p>Development at this site should not increase flood risk either on or off site. The design of the surface water management proposals should take into account the impacts of future climate change over the projected lifetime of the development.</p> <p>Proposed SuDS should be discussed with relevant stakeholders (LPA, LLFA and EA) at an early stage to understand possible opportunities and constraints.</p> <p>The following techniques are considered suitable for the site:</p> <ul style="list-style-type: none"> • Most source control techniques are likely to be suitable. Mapping suggests that permeable paving may have to use non-infiltrating systems given the possible risk from groundwater. • Infiltration may be suitable. Mapping suggests a medium risk of groundwater flooding and underlying soils may be permeable. Further site investigation should be carried out to assess potential for drainage by infiltration. If infiltration is suitable it should be avoided in areas where the depth to the water table is <1m. • Mapping suggests that the site slopes are suitable for all forms of detention. A liner maybe required due to the site potential groundwater flooding. • All filtration techniques are likely to be suitable. A liner maybe required to prevent the egress of groundwater. • All forms of conveyance are likely to be suitable. Where the slopes are >5% features should follow contours or utilise check dams to slow flows. A liner maybe required to prevent the egress of groundwater.

Charnwood Borough Council Strategic Flood Risk Assessment Level 2 Detailed Site Summary Tables



Site details	Site Code	PSH120
	Address	Land east of Leicester Road
	Area	38.70 ha
	Current land use	Greenfield
	Proposed land use	Residential
NPPF and planning implications	Exception Test requirements	<p>The Local Authority have carried out the Sequential Test in line with national guidance. The Sequential Test will need to be satisfied based on fluvial and other sources of flood risk before the Exception Test is applied. Residential development is classified as 'More Vulnerable'.</p> <p>It is recommended that proposed development will be sequentially located within Flood Zone 1 areas of the site, which may need to be confirmed through a site-specific assessment and more detailed modelling.</p> <p>The Exception test will need to be applied if:</p> <ul style="list-style-type: none"> • More Vulnerable and Essential Infrastructure development is located in FZ3a and for Highly Vulnerable development located in FZ2. • Highly Vulnerable infrastructure should not be permitted within FZ3a and FZ3b. • More Vulnerable and Less Vulnerable Infrastructure should not be permitted within FZ3b. <p>Development will not be permitted for the following scenario:</p> <ul style="list-style-type: none"> • Highly vulnerable development within FZ3a. • Highly vulnerable, More vulnerable and / or Less vulnerable development within FZ3b.

	<p>Requirements and guidance for site-specific Flood Risk Assessment</p>	<p>Flood Risk Assessment:</p> <ul style="list-style-type: none"> • At the planning application stage, a site-specific Flood Risk Assessment will be required for this site as development is located within Flood Zone 3b and may be subject to other sources of flooding and the development may introduce a more vulnerable use. It will also be required where development sites: <ul style="list-style-type: none"> ○ are 1 hectare or more in size; ○ contain land which has been identified by the Environment Agency as having critical drainage problems; or ○ contain land identified in the strategic flood risk assessment as being at increased flood risk in future. • Other sources of flooding must be considered as part of any site-specific Flood Risk Assessment, including surface water and groundwater. • Consideration should be given to the potential effects of climate change, particularly with respect to surface water. Proposals should consider the opportunity to include measures that provide for a reduction in the predicted surface water flood risk at existing development. • A more detailed hydraulic model may be required at Flood Risk Assessment stage, to confirm flood risk and flow paths, FZ3b and climate change extents from the watercourse, using channel topographic survey. • Climate change modelling should be undertaken using the relevant allowances for the type of development and level of risk. • Where there is a reasonable likelihood of multiple sources of flood risk having significant impact in combination it is recommended that consideration is given to assessing the combined risks of these. • Any FRA should be carried out in line with the National Planning Policy Framework Flood Risk and Coastal Change Planning Practice Guidance, Charnwood Council's Local Plan policies and the LLFA's SuDS guidance. <p>Consultation with the Local Authority, Local Lead Flood Authority and the Environment Agency should be undertaken at an early stage.</p> <ul style="list-style-type: none"> • The development should be designed using a sequential approach. Development should be steered away from areas of fluvial flood risk and surface water flow routes, preserving these spaces as green infrastructure. Development must be in line with Table 3: flood risk vulnerability and flood zone compatibility of the NPPG. • Development in FZ3b should be avoided unless appropriate use can be demonstrated in line with NPPF. • Development in FZ3 may require floodplain compensation and this should be confirmed with the EA at FRA stage. <p>Guidance for site design and making development safe:</p> <ul style="list-style-type: none"> • The developer will need to show, through an FRA, that future users of the development will not be placed in danger from flood hazards throughout its lifetime. It is for the applicant to show that the development meets the objectives of the NPPF's policy on flood risk. For example, how the operation of any mitigation measures can be safeguarded and maintained effectively through the lifetime of the development. (Para 048 Flood Risk and Coastal Change PPG). • Safe access and egress will need to be demonstrated in the 1 in 100-year plus climate change fluvial and rainfall events,
--	---	--

		<p>using the depth, velocity and hazard outputs. Raising of access routes must not impact on surface water flow routes. Consideration should be given to the siting of access points with respect to areas of surface water flood risk.</p> <ul style="list-style-type: none"> • Resilience measures will be required if buildings are situated in the flood risk area. Raising Finished Floor Levels above the design event may remove the need for resilience measures. • The risk from surface water flow routes should be quantified as part of a site-specific FRA, including a drainage strategy, to ensure that runoff from the development is not increased by placing development across any ephemeral surface water flow routes. A drainage strategy should help inform site layout and design to ensure there is no increase in runoff beyond the current greenfield rates. • On site attenuation schemes would need to be tested against the watercourse to ensure flows are not exacerbated downstream within the catchment. • New or re-development should adopt exemplar source control SuDS techniques to reduce the risk of frequent low impact flooding due to post-development runoff. Assessment for runoff should include allowance for climate change effects. • New development must seek opportunities to reduce overall level of flood risk at the site, for example by: <ul style="list-style-type: none"> ○ Reducing volume and rate of runoff ○ Relocating development to zones with lower flood risk ○ Creating space for flooding. • All development should adopt source control SuDS techniques to reduce the risk of frequent low impact flooding due to post development runoff. • SuDS should be designed to deliver multiple benefits including water quality, biodiversity, amenity, green infrastructure etc. Example features include swales, attenuation features, green roofs, rainwater capture and reuse and permeable paving. • Green infrastructure should be considered within the mitigation measures for surface water runoff from potential development and consider using Flood Zones 2 and 3 as public open space. • Efforts should be made to limit runoff to greenfield rates and discharge rates from the site should not increase downstream flood risk.
<p>Key messages</p>	<p>The flood risk element of the Exception Test is likely to be passed if:</p> <ul style="list-style-type: none"> • Development is limited to the 75% of the site outside of the Risk of Flooding from Surface Water zones and within Flood Zone 1. Development should therefore be steered away from the watercourses, preferable near safe access routes. • Areas in Flood Zone 2 are used for the least vulnerable parts of the development in accordance with Table 2 in the NPPF. No residential development is permitted in Flood Zone 3 and no development at all is permitted in Flood Zone 3b. • Detailed hydraulic modelling will need to be conducted for the unnamed watercourse that intersects the site to assess the present and future fluvial risk to the site. • If flood mitigation measures are implemented then they are tested to ensure that they will not displace water elsewhere (for example, if land is raised to permit development on one area, compensatory flood storage will be required in another). • Space for green infrastructure should be considered in the areas of highest flood risk. 	

Charnwood Borough Council Strategic Flood Risk Assessment Level 2 Detailed Site Summary Tables



Site details	Site Code	PSH120
	Address	Land east of Leicester Road
	Area	38.70 ha
	Current land use	Greenfield
	Proposed land use	Residential
		<ul style="list-style-type: none"> The ordinary watercourses bisect the site, so consideration regarding access is required for the portion of the site north of the watercourse, which is also bound by a railway line. Refer to the 'detailed guidance for developers' section (above) for further information on the measures that are appropriate for this site.
Mapping Information		
The key datasets used to make planning recommendations regarding this site was the Environment Agency's Risk of Flooding from Surface Water mapping. More details regarding data used for this assessment can be found below.		
Flood Zones	<p>Flood Zones 2 and 3 have been taken from the Environment Agency's Flood Zones (2020) and detailed modelling where present for Flood Zone 3b. In the absence of modelling, Flood Zone 3a has been used as an indication of Flood Zone 3b.</p> <p>It is recommended that a more detailed hydraulic model is constructed at the site-specific Flood Risk Assessment stage, to confirm flood risk.</p>	
Climate change	Climate change was based on Flood Zone 2 to serve as an indication of possible extents. It is recommended that the latest EA's climate change allowances are modelled in a detailed hydraulic model as part of a site-specific Flood Risk Assessment.	
Fluvial depth, velocity and hazard mapping	There is no available corresponding fluvial modelling data from the generalised 2D model; therefore, the Risk of Flooding from Surface Water mapping can be used as this represents the floodplains of small watercourses. This should be explored further at the site-specific stage.	
Surface Water	The Risk of Flooding from Surface Water has been used to define areas at risk from surface water flooding.	
Surface water depth, velocity and hazard mapping	The surface water depth, velocity and hazard mapping for the 1 in 30-year (high risk), 1 in 100-year (medium risk) and 1 in 1,000-year (low risk) events is taken from the Environment Agency's Risk of Flooding from Surface Water mapping.	